



PDC & ADC Domestic Immersion Heaters

Immersion heaters in the most popular sizes for domestic hot water cylinder heating.

Key Features

- Dual cut-out immersion heaters with standard 2¼" BSP boss fitting
- Supplied with both a fitted rod thermostat and secondary manual reset safety cut-out
- Comply with the European safety standard EN 60335-2-73
- Available with popular copper or Aqualoy sheathed elements
- Aqualoy is a scale resistant material for use in more aggressive hard water areas
- 2 year UK guarantee for models: 33324601, 33324602, 33324701
- 1 year UK guarantee for models: 33324501, 33324502, 33324503



Catalogue Number	Model/Description
33324501	P11DC 11" 2¼" BSP Copper
33324502	P14DC 14" 2¼" BSP Copper
33324503	P27DC 27" 2¼" BSP Copper
33324601	A11DC 11" 2¼" BSP Aqualoy
33324602	A27DC 27" 2¼" BSP Aqualoy
33324701	GU11DC 11" 1¾" BSP Unvented Aqualoy

Technical Information	
Immersion Heaters	11, 14 or 27 inches
Cable Connection	Cut-out in lid
Power	3kW @ 240V
Boss Thread	21/4" BSP
Sheath Material	Copper or Incoloy 800
Approvals	WRAS, BEAB & CE mark

