

Selectronic Premier Electric Showers

Trusted by UK care industry professionals, Selectronic Premier thermostatic showers offer unrivalled instant electric shower temperature control accuracy and temperature lock options to ensure a comfortable and safe showering experience for all users.

Key Features

- Smooth contoured styling with high contrast controls for ease of visibility
- Highly accurate, temperature control to +/- 0.5°C for comfortable safe showering
- Large LED digital temperature display
- All push-button controlled with tactile identification coding for ease of use
- Audible feedback for confirmation of adjustment and operation status
- Phased shutdown safety protection for next user cool start up and scale protection
- 3 temperature range limiter lock options (34-40°C), (34-41°C), (34-43°C) or unlocked (25-46°C) set at installation
- Simple single push button rapid commissioning
- Data logging for access to user and performance analysis, with diagnostic mode to assist service engineers
- IPX5 rated protection for installation in wet room zones
- A energy efficiency rated
- Free 5 year UK manufacturers guarantee (Product registration is required)

All models have enhanced shower accessories

- Stainless steel riser rails replace aluminium ones
- Sturdy 4-point fixing riser rail wall brackets
- A combined riser/grab rail with reinforced metal bracket plates (on PLUS and WPC models) The grab rail is tested and approved for 250kg static load (subject to wall material strength and the correct fixings being used by the installer)
- New wireless connectivity for automatic operation of compatible level access waste pumps (WPC models only)
- An optional remote control kit to start and stop the shower from outside the showering area which can be retro-fitted to all Selectronic Premier showers is also available (RSSSRC - see page 12)



Premier STANDARD

- 5 spray-mode showerhead
- 540mm stainless steel riser rail with 4-point fixing brackets
- 1.25 metre flexible anti-kink hose
- Adjustable showerhead riser clamp
- Soap dish and hose retention ring



The new generation of Selectronic Premier showers meets the very latest and highest level of industry safety standards and is endorsed by leading care professional bodies.



Premier PLUS

- 5 spray-mode showerhead
- 1 metre 250kg* load stainless steel riser grab rail with metal reinforced brackets
- 2 metre flexible anti-kink hose
- Adjustable showerhead riser clamp
- Soap dish and hose retention ring

* The grab rail duty is subject to wall material strength and the correct fixings being used by the installer



Premier WPC

- 5 spray-mode showerhead
- 1 metre 250kg* load stainless steel riser grab rail with metal reinforced brackets
- 2 metre flexible anti-kink hose
- Adjustable showerhead riser clamp
- Soap dish and hose retention ring
- Includes a RF receiver module and integral shower PCB for wireless connection to all leading brand level access waste pumps (The pump and drain kit are not supplied).

Technical Information	
Water	Operating Pressure 0.7 - 10bar (10 - 140psi)
Entry Points	3 cable & 3 water (top, bottom or rear on the right hand side)
Cold Water Connection	15mm compression nut and olive to inlet fitting of the shower

Catalogue Number	Model/Description
100054	RSELP85S Selectronic Premier STANDARD 8.5kW
100061	RSELP95S Selectronic Premier STANDARD 9.5kW
100078	RSELP108S Selectronic Premier STANDARD 10.8kW

Catalogue Number	Model/Description
100085	RSELP85P Selectronic Premier PLUS 8.5kW
100092	RSELP95P Selectronic Premier PLUS 9.5kW
100108	RSELP108P Selectronic Premier PLUS 10.8kW

Catalogue Number	Model/Description
100115	RSELP85WPC Selectronic Premier WPC (waste pump connectivity) 8.5kW
100112	RSELP95WPC Selectronic Premier WPC (waste pump connectivity) 9.5kW