

TS Stored Water Heaters

Quickly and effectively provide hot water on demand for up to four outlets.

Key Features

- Hot water on demand for up to four outlets
- Adjustable rotary thermostat with 'heating' LED indicator
- Maximum temperature 70°C with 60°C Eco setting and frost protection
- Glass ceramic water tank with magnesium sacrificial anode protection
- Supplied with accompanying pressure relief valve, dielectric connectors and wall mounting hooks
- Thermal insulation 20mm ±4mm and stainless steel water outlet
- Removable flange for easy access to magnesium anode and heating element
- C Energy Rating
- 1 year UK manufacturer guarantee



Thermostatic Blending Valve



Cold Water Control Pack: expansion vessel, PRV, check valve



Tundish

C

Product Dimensions

10L

15L



410mm



370mm

370mm

Product depth: 250mm

Product depth: 310mm

In small unvented water heaters the hot water expansion can often be accommodated back into the cold water mains supply, as indicated in the Water Regulations. Where this is not possible the installer will need to fit a set of cold water controls.

Catalogue Number	Model/Description
47789501	TS10 10Ltr Stored Water Heater 2kW
47789601	TS15 15Ltr Stored Water Heater 2kW
Accessories	
87783101	CWP Cold Water Control Pack
87783103	TBV Thermostatic Blending Valve
97783236	TUN Tundish 1/2" male 3/4" female

Technical Information	
Capacity	10 Litres & 15 Litres
Cable Connection	Supplied with fitted 1.5m cable and UK plug
Power	2kW @240V
Water	Maximum operating pressure 6bar (87psi) - 1/2" BSP connections
Approvals	CE mark
Ingress Protection	IPX4

